



Printing date 07/02/2024 Version 6.0 Last revision 06/01/2024

1 Identification

- · Product name: Alumina Polishing Suspension, De-agglomerated, 0.05 micron and High Purity, De-agglomerated 0.05 5 micron
- Part number: 90-187505, 90-187540, 90-187575, 90-187506, 90-187511, 90-187516, 90-187521, 90-187526
- · Application of the substance / the mixture Polishing solution
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Allied High Tech Products Inc. 16207 Carmenita Road

USA-Cerritos, CA, 90703

USA

in fo@allied high tech.com

- · Information department: Product safety department
- · Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- · Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).
- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous components and components with occupational exposure limits:		
57-55-6 propylene glycol	5-15%	
1344-28-1 aluminium oxide	5-15%	
· Non-hazardous components:		
Proprietary Ingredient	70-90%	

· Additional information: The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 2)

Printing date 07/02/2024 Version 6.0 Last revision 06/01/2024

Product name: Alumina Polishing Suspension, De-agglomerated, 0.05 micron and High Purity, De-agglomerated 0.05 - 5 micron

(Contd. of page 1)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Eye irritation

Dermatitis

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures necessary.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

No special requirements.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No additional data. See 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:			
57-55-0	57-55-6 propylene glycol		
WEEL Long-term value: 10 mg/m³			
1344-28-1 aluminium oxide			
PEL	Long-term value: 15*; 5** mg/m³ *Total dust; ** Respirable fraction		
REL	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.		
	Long-term value: 1* mg/m³ as Al; *as respirable fraction, A4		

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed.

Product name: Alumina Polishing Suspension, De-agglomerated, 0.05 micron and High Purity, De-agglomerated 0.05 - 5 micron

(Contd. of page 2)

· Breathing equipment:

Not required.

Use suitable respiratory protective device in case of insufficient ventilation.

- · Protection of hands: Not required.
- · Material of gloves Nitrile rubber, NBR
- · Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties · General Information · Appearance:		
Form:	Suspension	
Color:	Whitish	
· Odor:	Odorless	
0 4-0-1	Not determined.	
· Odor threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	5-7	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
· Density:	Not determined.	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
*	Not determined.	
· Solubility in / Miscibility with Water:	Fully miscible.	
· Partition coefficient (n-octanol/water)): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	4.2-12.5 %	
VOC content:	4.17-12.5 %	
Solids content:	87.5 %	
· Other information	Other information No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

Printing date 07/02/2024 Version 6.0 Last revision 06/01/2024

Product name: Alumina Polishing Suspension, De-agglomerated, 0.05 micron and High Purity, De-agglomerated 0.05 - 5 micron

(Contd. of page 3)

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Keep away from heat.

Keep away from oxidising agents and acidic substances.

Keep away from open flames. - No smoking.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

· Additional information: Hazardous decomposition products may form during combustion.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
57-55-6	57-55-6 propylene glycol		
Oral	LD50 >2,000 mg/kg (rat)		
Dermal	LD50 20,800 mg/kg (rabbit)		
1344-28	1344-28-1 aluminium oxide		
Oral	LD50 >5,000 mg/kg (rat)		

- · Primary chemical irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Abrasive eye irritant

Abrasive skin irritant

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability Not easily biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential Non significant accumulation in organisms
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

Printing date 07/02/2024 Version 6.0 Last revision 06/01/2024

Product name: Alumina Polishing Suspension, De-agglomerated, 0.05 micron and High Purity, De-agglomerated 0.05 - 5 micron

(Contd. of page 4)

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADN, IMDG, IATA	not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated	
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA · Class	not regulated	
· Packing group · DOT, IMDG, IATA	not regulated	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		
· UN "Model Regulation":	not regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- No further relevant information available

The further relevant information available.		
· Sara		
· Section 355 (extremely hazardous substances):		
None of the ingredients is listed.		
· Section 313 (Specific toxic chemical listings):		
1344-28-1 aluminium oxide		
· TSCA (Toxic Substances Control Act):		
All components have the value ACTIVE.		

- · Hazardous Air Pollutants
- None of the ingredients is listed. Proposition 65
- Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Printing date 07/02/2024 Version 6.0 Last revision 06/01/2024

Product name: Alumina Polishing Suspension, De-agglomerated, 0.05 micron and High Purity, De-agglomerated 0.05 - 5 micron

(Contd. of page 5)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

To the best of our knowledge, the information contained herein is accurate. However, it does not describe a guarantee of product properties and does not establish a contractual legal relationship.

· Department issuing SDS: Technical Services

· Contact: Pablo Mendoza

· Last revision / supersedes version: 06/01/2024 / 5.0

· Supersedes date: 06/01/2020 · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

* * Data compared to the previous version altered.