



## 1 Identification

· Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

· Part number: 200-10004

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Allied High Tech Products Inc.

16207 Carmenita Road USA-Cerritos, CA, 90703

USA

info@alliedhightech.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

### 2 Hazard(s) identification

### · Classification of the substance or mixture



Flammable Aerosols 2 H223 Flammable aerosol.



GHS04 Gas cylinder

Gases under Pressure - Compressed gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Toxicity - Dermal 4	H312	Harmful in contact with skin.
Skin Irritation 2	H315	Causes skin irritation.
Eye Irritation 2A	H319	Causes serious eye irritation.
Specific Target Organ Toxicity - Single Exposure	3 Н335-Н3	36 May cause respiratory irritation. May cause drowsiness or dizziness

· Label elements

<sup>·</sup> GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

#### Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

(Contd. of page 1)

### · Hazard pictograms





· Signal word Danger

#### · Hazard-determining components of labeling:

1-bromopropane

Distillates (petroleum), hydrotreated light

#### · Hazard statements

Flammable aerosol.

Contains gas under pressure; may explode if heated.

Harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May damage fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash contaminated body parts thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye protection / face protection.

Use personal protective equipment as required.

If on skin: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazard	us components and components with occupational exposure limits:	
106-9	I-5 1-bromopropane	75-85%
	Flammable Liquids 2, H225; Carcinogenicity 2, H351; Toxic to Reproduction 1B, H360; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	
68476-8	6-8 Petroleum gases, liquefied, sweetened      Flammable Gases 1, H220;    Gases under Pressure - Compressed gas, H280;    Germ Cell Mutagenicity 1B, H340; Carcinogenicity 1A, H350	8-15%

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

	(Contd. of page 2)
64742-47-8 Distillates (petroleum), hydrotreated light	1-5%
Flammable Liquids 3, H226; Aspiration Hazard 1, H304; Specific Target Organ Toxicity - Single Exposure 3, H336	
· Non-hazardous components:	
Proprietary Ingredient	1-5%

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Nausea

Dermatitis

Eve irritation

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- Precautions for safe handling

Protect from heat and direct sunlight.

Ensure proper ventilation/exhaustion at workplaces.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurized containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No additional data. See 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

	1
106-94-5 1-bromopropane	
TLV Long-term value: 0.1 ppm	
A3	

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

selection of the grove material on consideration of the penetration times, rates of unfusion and the deg

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eye protection:

Safety glasses



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Color: White
Odor: Mild

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

	(Contd. of pag
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	<-45 °C (<-49 °F) 39-87 °C (102.2-188.6 °F)
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Auto igniting:	490 °C (914 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure at 20 °C (68 °F): · Vapor pressure at 50 °C (122 °F):	78.7 hPa (59 mm Hg) 500 hPa (375 mm Hg)
· Density:	Not determined.
Bulk density: Relative density Vapor density Evaporation rate	1 kg/m³ Not determined. Not determined. Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: VOC content:	0.91-4.55 %
Solids content:	0.0 %
· Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

(Contd. of page 5)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values tha	t are relevant for classification:	
106-94-5	1-bromopi	ropane	
Inhalative	LC50/4 h	253 mg/l (rat)	
64742-47-8 Distillates (petroleum), hydrotreated light			
Dermal	LD50	3,160 mg/kg (rabbit)	

- · Primary chemical irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eve: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Specific Target Organ Toxicity - Single Exposure 3 - Target Organ: central nervous system depression

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
106-94-5 1-bromopropane	2B
· NTP (National Toxicology Program)	
106-94-5 1-bromopropane	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

## 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

- · UN-Number
- · DOT, IMDG, IATA UN1950
- · UN proper shipping name
- $\cdot$  DOT Aerosols, flammable

*Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024* 

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

(Contd. of page 6)

	(Contd. of page 6)
· IMDG · IATA	AEROSOLS AEROSOLS, flammable
· Transport hazard class(es)	AEROSOLS, Hallillaule
· DOT	
· DO1	
· Class	2.1 Gases
· Label	2.1
· IMDG, IATA	
· Class · Label	2.1 Gases 2.1
· Packing group	2.1
· DOT, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases
Hazard identification number (Kemler code):	- P.O.H.
· EMS Number: · Stowage Code	F-D,S-U SW1 Protected from sources of heat.
Stowage Code	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category
	A. For AEROSOLS with a capacity above 1 litre: Category B. For
	WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for
	division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
<ul> <li>Transport in bulk according to Annex II of MARPOL73/78 at the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· Limited quantities (LQ)	1L
· Transport category	2
Tunnel restriction code	D
· IMDG	11
· Limited quantities (LQ)	1L Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1
O. Model Regulation (	(Contd. on page 8)

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

(Contd. of page 7)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- No further relevant information available.
- ·Sara

· Section 355	(extremely	hazardous	substances	):

None of the ingredients is listed.

#### · Section 313 (Specific toxic chemical listings):

106-94-5 1-bromopropane

#### · TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

#### · Hazardous Air Pollutants

106-94-5 1-bromopropane

· Proposition 65

#### · Chemicals known to cause cancer:

106-94-5 1-bromopropane

#### Chemicals known to cause reproductive toxicity for females:

106-94-5 1-bromopropane

#### · Chemicals known to cause reproductive toxicity for males:

106-94-5 1-bromopropane

#### · Chemicals known to cause developmental toxicity:

106-94-5 1-bromopropane

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

To the best of our knowledge, the information contained herein is accurate. However, it does not describe a guarantee of product properties and does not establish a contractual legal relationship.

- · Department issuing SDS: Technical Services
- · Contact: Pablo Mendoza
- · Last revision / supersedes version: 06/01/2024 / 1.0
- · Supersedes date: 10/10/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Gases 1: Flammable gases - Category 1

Flammable Aerosols 2: Aerosols – Category 2

Gases under Pressure - Compressed gas: Gases under pressure - Compressed gas

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Dermal 4: Acute toxicity - Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Printing date 07/02/2024 Version 2.0 Last revision 06/01/2024

Product name: Mold Release Spray, Aerosol Spray (Hot Mouting)

(Contd. of page 8)

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1A: Carcinogenicity – Category 1A

Carcinogenicity 2: Carcinogenicity – Category 2
Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

\* \* Data compared to the previous version altered.