

Page 1/8

Printing date 07/02/2024

Version 4.0

Last revision 06/01/2024

* 1 Identification

· Product name: Mounting Wax, Hot

· Part number: 71-10040, 71-10050

ligh tach paopud

· Application of the substance / the mixture Adhesives

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Allied High Tech Products Inc. 16207 Carmenita Road

16207 Carmenita Road USA-Cerritos, CA, 90703

USA

info@alliedhightech.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Sensitization - Respiratory 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Eye Damage 1 H318 Causes serious eye damage.



Skin Irritation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

(Contd. of page 1)

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

phthalic anhydride

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous components and components with occupational exposure limits:		
85-44-9	phthalic anhydride	60-70%
	Sensitization - Respiratory 1, H334; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	
		30-40%
	♦ Acute Toxicity - Oral 4, H302	

· Additional information: The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Breathing difficulty

Dizziness

Coughing

Allergic reactions

Nausea

Dermatitis

Eve irritation

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Dust well.

Ensure proper ventilation/exhaustion at workplaces.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Suitable material for receptacles and pipes: steel or stainless steel.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No additional data. See 7.

(Contd. on page 4)

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:				
85-44-9	85-44-9 phthalic anhydride			
PEL	Long-term value: 12 mg/m³, 2 ppm			
REL	REL Long-term value: 6 mg/m³, 1 ppm			
TLV	Short-term value: 0.005* mg/m³ Long-term value: 0.002* 0.05** mg/m³ A4,Skin;DSEN,RSEN,*inh&vapor**SL: mg/100cm2			
107-21	07-21-1 ethylene glycol			
TLV	Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only, A4			
WEEL	I (2)			

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eve protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid
Color: Clear
Odor: Odorless
Odor threshold: Not determined.

· **pH-value:** Not applicable.

(Contd. on page 5)

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

(Contd. of page 4)

	(Contd. of page 4
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	68-74 °C (154.4-165.2 °F) >100 °C (>212 °F)
· Flash point:	>263 °C (>505.4 °F)
· Flammability (solid, gaseous):	Not determined.
· Auto igniting:	580 °C (1,076 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	1.7 Vol % 10.5 Vol %
· Vapor pressure:	Not applicable.
 Density at 20 °C (68 °F): Relative density Vapor density Specific gravity: Evaporation rate 	1.435 g/cm³ (11.975 lbs/gal) Not determined. >1.0 1.31 Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.
· Solvent content: VOC content:	30.77 %
Solids content:	69.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Keep away from heat.

Keep away from open flames. - No smoking.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide
- · Additional information: Hazardous decomposition products may form during combustion.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	· LD/LC	· LD/LC50 values that are relevant for classification:	
ATE (Acute Toxicity Estimate)		oxicity Estimate)	
	Oral	LD50	6,067 mg/kg (rat)

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

(Contd. of page 5)

85-44-9 p	85-44-9 phthalic anhydride	
Oral LD50 4,200 mg/kg (rat)		
107-21-1 ethylene glycol		
Oral L	LD50 5,840 mg/kg (rat)	
Dermal L	LD50 9,430 mg/kg (rabbit)	

- · Primary chemical irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· IIN-Number

, , ,	<u> </u>
· DOT, ADN, IMDG, IATA	not regulated
Civilanibei	

· UN proper shipping name

· DOT, ADN, IMDG, IATA not regulated

(Contd. on page 7)

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

(Contd. of page 6)

	(Colin	i. of page of
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA		
· Class	not regulated	
· Packing group		
· DOT, IMDG, IATA	not regulated	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MARPOL73/78 and		
the IBC Code	Not applicable.	
· UN "Model Regulation":	not regulated	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

107-21-1 ethylene glycol

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

To the best of our knowledge, the information contained herein is accurate. However, it does not describe a guarantee of product properties and does not establish a contractual legal relationship.

- · Department issuing SDS: Technical Services
- · Contact: Pablo Mendoza
- · Last revision / supersedes version: 06/01/2024 / 3.0
- · Supersedes date: 06/01/2022
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

Printing date 07/02/2024 Version 4.0 Last revision 06/01/2024

Product name: Mounting Wax, Hot

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Oral 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - Respiratory 1: Respiratory sensitisation - Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

(Contd. of page 7)