

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

### \* 1 Identification

- **Product name:** QuickMount Acrylic Liquid
- **Part number:** 140-10035
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Allied High Tech Products Inc.  
16207 Carmenita Road  
USA-Cerritos, CA, 90703  
USA  
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (310) 635-2466  
Chemtrec: +1 (202) 483-7616

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the lung, the kidneys, the liver and the heart through prolonged or repeated exposure.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Skin Irritation 2

H315 Causes skin irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

**Product name: QuickMount Acrylic Liquid**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** Warning**· Hazard-determining components of labeling:**

methyl methacrylate  
N,N-dimethyl-p-toluidine  
1,3-Butanediol dimethacrylate

**· Hazard statements**

Flammable liquid and vapor.  
Harmful if inhaled.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Suspected of causing cancer.  
May cause respiratory irritation.  
May cause damage to the lung, the kidneys, the liver and the heart through prolonged or repeated exposure.

**· Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Get medical advice/attention if you feel unwell.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition/information on ingredients

**· Chemical characterization: Mixtures****· Description:** Mixture of the substances listed below with nonhazardous additions.**· Hazardous components and components with occupational exposure limits:**

80-62-6	methyl methacrylate	90-100%
	Flammable Liquids 2, H225;  Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

**Product name: QuickMount Acrylic Liquid**

(Contd. of page 2)

1189-08-8	1,3-Butanediol dimethacrylate ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	5-<10%
99-97-8	N,N-dimethyl-p-toluidine ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; ⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Flammable Liquids 4, H227; Aquatic Chronic 3, H412	1-<2.5%

### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Headache

Dizziness

Coughing

Allergic reactions

Nausea

Dermatitis

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:**

Mouth respiratory protective device.

Wear fully protective suit.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

**Product name: QuickMount Acrylic Liquid**

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Protect from heat and direct sunlight.  
Ensure proper ventilation/exhaustion at workplaces.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No additional data. See 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

80-62-6 methyl methacrylate	
PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4
99-97-8 N,N-dimethyl-p-toluidine	
WEEL	Long-term value: 0.5 ppm

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**



Protective gloves

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

### Product name: QuickMount Acrylic Liquid

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form: Liquid

Color: Clear

· Odor: Acrylic

· Odor threshold: 0.049 ppm

· pH-value: Not determined.

#### · Change in condition

Melting point/Melting range: -48 °C (-54.4 °F)

Boiling point/Boiling range: 101 °C (213.8 °F)

· Flash point: 55 °C (131 °F)

· Flammability (solid, gaseous): Flammable.

· Auto igniting: 430 °C (806 °F)

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Not determined.

#### · Explosion limits:

Lower: 2.1 Vol %

Upper: 12.5 Vol %

· Vapor pressure at 20 °C (68 °F): 47 hPa (35.3 mm Hg)

· Density: Not determined.

· Relative density: Not determined.

· Vapor density at 20 °C (68 °F): 3.5 g/cm<sup>3</sup> (29.208 lbs/gal)

· Specific gravity: 0.936 (water = 1)

· Evaporation rate: Not determined.

#### · Solubility in / Miscibility with

Water: Partly soluble.

· Partition coefficient (n-octanol/water): Not determined.

#### · Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

Product name: QuickMount Acrylic Liquid

(Contd. of page 5)

· <b>Solvent content:</b>	
· <b>VOC content:</b>	0.00 %
· <b>Solids content:</b>	7.6 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**  
Keep away from oxidising agents and acidic substances.  
Keep away from heat.  
Keep away from open flames. - No smoking.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide
- **Additional information:** Hazardous decomposition products may form during combustion.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimate)</b>		
Oral	LD50	86,623 mg/kg (rat)
Dermal	LD50	15,750 mg/kg
Inhalative	LC50/4 h	15.7 mg/l (rat)

#### 80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	18 mg/l (rat)

#### 99-97-8 N,N-dimethyl-p-toluidine

Oral	LD50	1,650 mg/kg (rat)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	1.4 mg/l (rat)

- **Primary chemical irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
80-62-6	methyl methacrylate	3
99-97-8	N,N-dimethyl-p-toluidine	2B

· <b>NTP (National Toxicology Program)</b>		
None of the ingredients is listed.		

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

Product name: QuickMount Acrylic Liquid

(Contd. of page 6)

· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>
None of the ingredients is listed.


### 12 Ecological information

· <b>Toxicity</b>
· <b>Aquatic toxicity:</b>
<b>80-62-6 methyl methacrylate</b>
EC50 (96 h)   170 mg/l (pseudokirchneriella subcapitata)
EC50 (48 h)   69 mg/l (daphnia)
LC50 (96 h)   79 mg/l (oncorhynchus mykiss)
<b>99-97-8 N,N-dimethyl-p-toluidine</b>
LC50 (96 h)   46 mg/l (pimephales promelas)
· <b>Persistence and degradability</b> No further relevant information available.
· <b>Behavior in environmental systems:</b>
· <b>Bioaccumulative potential</b> No further relevant information available.
· <b>Mobility in soil</b> No further relevant information available.
· <b>Additional ecological information:</b>
· <b>General notes:</b>
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
· <b>Results of PBT and vPvB assessment</b>
· <b>PBT:</b> Not applicable.
· <b>vPvB:</b> Not applicable.
· <b>Other adverse effects</b> No further relevant information available.

### 13 Disposal considerations

· <b>Waste treatment methods</b>
· <b>Recommendation:</b> Contact waste processors for recycling information.
· <b>Uncleaned packagings:</b>
· <b>Recommendation:</b> Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, IMDG, IATA</b>	UN1247
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Methyl methacrylate monomer, stabilized
· <b>IMDG, IATA</b>	METHYL METHACRYLATE MONOMER, STABILIZED
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS


Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

Product name: QuickMount Acrylic Liquid

(Contd. of page 7)

· <b>IMDG, IATA</b> 	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Hazard identification number (Kemler code):</b>	30
· <b>EMS Number:</b>	F-E,S-D
· <b>Stowage Category</b>	B
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· <b>Limited quantities (LQ)</b>	1L
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D/E
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 | methyl methacrylate

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

80-62-6 | methyl methacrylate

· **Proposition 65**

· **Chemicals known to cause cancer:**

99-97-8 | N,N-dimethyl-p-toluidine

(Contd. on page 9)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 2.0

Last revision 06/01/2024

**Product name: QuickMount Acrylic Liquid**

(Contd. of page 8)

· <b>Chemicals known to cause reproductive toxicity for females:</b>
None of the ingredients is listed.
· <b>Chemicals known to cause reproductive toxicity for males:</b>
None of the ingredients is listed.
· <b>Chemicals known to cause developmental toxicity:</b>
None of the ingredients is listed.
· <b>Chemical safety assessment:</b> A Chemical Safety Assessment has not been carried out.

### 16 Other information

To the best of our knowledge, the information contained herein is accurate. However, it does not describe a guarantee of product properties and does not establish a contractual legal relationship.

· **Department issuing SDS:** Technical Services

· **Contact:** Pablo Mendoza

· **Last revision / supersedes version:** 06/01/2024 / 1.0

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**