

Safety Data Sheet acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

* 1 Identification

- **Product name:** RedLube Polishing Lubricant
- **Part number:** 90-206995 - 90-207010
- **Application of the substance / the mixture** Lubricant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
16207 Carmenita Road
USA-Cerritos, CA, 90703
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system.



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Eye Irritation 2B

H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 1)

· **Signal word** Danger· **Hazard-determining components of labeling:**

methyl alcohol

· **Hazard statements**

Flammable liquid and vapor.

Harmful if swallowed.

Causes eye irritation.

Causes damage to the central nervous system.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see on this label).

Rinse mouth.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.




Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Hazardous components and components with occupational exposure limits:**

57-55-6	propylene glycol	80-90%
67-56-1	methyl alcohol	10-20%
	 Flammable Liquids 2, H225;  Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331;  Specific Target Organ Toxicity - Single Exposure 1, H370	

· **Non-hazardous components:**

7632-00-0	sodium nitrite	 Oxidizing Solids 3, H272;  Acute Toxicity - Oral 3, H301;  Aquatic Acute 1, H400	<0.25%
-----------	----------------	--	--------

· **Additional information:** The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** Immediately rinse with water.· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.· **After swallowing:** Immediately call a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 - Gastric or intestinal disorders
 - Disorientation
 - Unconsciousness
 - Breathing difficulty
 - Headache
 - Dizziness
 - Coughing
 - Nausea
 - Eye irritation
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation
 - Keep away from ignition sources
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Do not allow to enter sewers/ surface or ground water.
 - Prevent seepage into sewage system, workpits and cellars.
 - Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Protect from heat and direct sunlight.
 - Ensure proper ventilation/exhaustion at workplaces.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - No special requirements.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 3)

- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No additional data. See 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
57-55-6 propylene glycol	
WEEL	Long-term value: 10 mg/m ³
67-56-1 methyl alcohol	
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEIc
· Ingredients with biological limit values:	
67-56-1 methyl alcohol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Liquid
Color:	Red
· Odor:	Mild
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
· Flash point:	43 °C (109.4 °F)
· Flammability (solid, gaseous):	Flammable.
· Auto igniting:	371 °C (699.8 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	12.6 Vol %
· Vapor pressure at 20 °C (68 °F):	0.1 hPa
· Density at 20 °C (68 °F):	1.004 g/cm ³ (8.378 lbs/gal)
· Relative density	Not determined.
· Vapor density	2.5
· Specific gravity:	1.018 (Water = 1)
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.9 %
VOC content:	99.91 %
Solids content:	0.1 %
· Other information	No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 5)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Keep away from heat.
Keep away from open flames. - No smoking.
Keep away from oxidising agents and acidic substances.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Aldehyde
Carbon monoxide and carbon dioxide
- **Additional information:** Hazardous decomposition products may form during combustion.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	734 mg/kg
Dermal	LD50	2,203 mg/kg
Inhalative	LC50/4 h	22 mg/l

57-55-6 propylene glycol

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

67-56-1 methyl alcohol

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary chemical irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant



(Contd. of page 6)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1987
· DOT, IMDG, IATA	
· UN proper shipping name	Alcohols, n.o.s. (Methanol)
· DOT	ALCOHOLS, N.O.S. (METHANOL)
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-D
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 7)

· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D/E

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S. (METHANOL), 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	
No further relevant information available.	
· Sara	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
67-56-1	methyl alcohol
7632-00-0	sodium nitrite
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
· Hazardous Air Pollutants	
67-56-1	methyl alcohol
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
67-56-1	methyl alcohol
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

To the best of our knowledge, the information contained herein is accurate. However, it does not describe a guarantee of product properties and does not establish a contractual legal relationship.

- **Department issuing SDS:** Technical Services
- **Contact:** Pablo Mendoza
- **Last revision / supersedes version:** 06/01/2024 / 4.0
- **Supersedes date:** 06/01/2022
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/02/2024

Version 5.0

Last revision 06/01/2024

Product name: RedLube Polishing Lubricant

(Contd. of page 8)

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1

*** Data compared to the previous version altered.**